

Modular Multiples®

Trimmed®
Recessed
New Work



This leaflet contains products covered under one or more of the following US Patent Numbers:

6,568,826B1	6,692,139B2
6,820,999B2	7,207,698B2
6,896,391B2	6,969,182B2
6,997,267B2	6,997,574B2
7,036,953B2	6,745,785B2
7,300,176B2	7,478,921B1
D520,666S	D530,038S
D537,553S	D819,857
D818,632	D818,624
D818,623	8,740,407
8,511,860	8,231,242
8,210,720	7,832,907

Modular International, Inc. produced a major portion of the lighting for the project shown. The photograph, however, is not intended to imply that the various owners of the projects endorse our products or use our products exclusively.

Modular International Inc.
3941 California Avenue
Pittsburgh, PA 15212
1-412-734-9000

www.modularinternational.com

Modular Multiples®

The Original Multiple Lamp Family of Fixtures

4

Trimmed

Recessed - New Work



- Configurations:**
- 1, 2, 3, 4 light units standard
 - Custom configurations available

- Housing:**
- Fabricated 18 gauge steel supplied with adjustable mounting brackets
 - 14 gauge steel trim flange
 - Available for airtight or IC rated applications

- Finishes:**
- Powder coated - white or black standard
 - Custom colors available
 - Stainless steel / satin nickel available

- Electrical:**
- Internal electronic power supply(s) / transformer(s) / ballast(s)
 - Dimmable (not applicable on HID products)
 - One power supply / transformer per lamp allowing for multi-circuit wiring.
 - 120v and 277v available
 - Listed to UL1598 standards

Lamping:

Standard LED Modules

6w LED-506-6	12w LED-512-12	12w LED-512-22
8w LED-708-6	14w LED-714-12	14w LED-714-22
16w LED-716-12	16w LED-716-22	16w LED-716-45
30w LED-930-12	30w LED-930-22	30w LED-930-45

Direct Replacement LED or Legacy Lamps:

MR16LED (BLD)	MR16 HALOGEN (B)	MR16CMH (BH)
AR111LED (DLD)	AR111 HALOGEN (D)	CDMR111 (S)
PAR30LED (GLD)	PAR30 (G)	PAR30HID (H)
PAR38LED (JLD)	PAR38 (J)	PAR38HID (K)

Mounting:


- For new construction applications.
- Recessed housing is installed via adjustable universal mounting brackets and bar hangers prior to the installation of drywall.
- Fixture designed for use in ceiling material with a maximum thickness of 2"

Options:






- Patented die-cast aluminum ring sets and locking devices
- Pull down yokes
- Shielding cones
- Filter media
 - LED modules accept one 1/8" thick filter
 - LED direct replacement and legacy lamps accept up to two 1/8" thick filters

**Model #
example:**

M-2-LED/16-x-TI-REC- TR





[Download CSI
drop-in spec template](#)



Modular Multiples®

Trimmed Typical Installation



Modular Multiples®

Trimmed

Recessed - New Work

Built to your specifications, these high-quality fixtures feature a trimmed aperture for a clean, refined appearance. Available with transformer incorporated, transformer attached, and remote transformer configurations for new and old work installations. The series is adaptable to plaster, gypboard, wood, or acoustical ceilings. This series conforms to USA standards. A companion series that conforms to Asian and European standards is also available.

One Lamp




M-1-B-2-TI-SQ-TR

Modular Multiples® Trimmed Series, one MR16 lamp, black housing, transformer incorporated, square aperture, trimmed configuration shown.

Other configurations available.

[Download CSI drop-in spec template](#)



LAMPS and DIMENSIONS	A	B	C	D	E	F	G
LED506, LED513 / MR16LED / MR16	3-3/8" 86mm	4-7/8" 124mm	3-3/8" 86mm	4-7/8" 124mm	8" 203mm	10-1/2" 267mm	8" 203mm
LED708, 714, 716, 930 / AR111LED / AR111	7-1/4" 184mm	9-1/4" 235mm	7-1/4" 184mm	9-1/4" 235mm	10-3/4" 273mm	1'1-3/4" 349mm	8-1/2" 216mm
PAR38LED / PAR38	7-1/4" 184mm	9-1/4" 235mm	7-1/4" 184mm	9-1/4" 235mm	10-3/4" 273mm	1'1-3/4" 349mm	8-1/2" 216mm

Modular Multiples®

Trimmed

Recessed - New Work

Built to your specifications, these high-quality fixtures feature a trimmed aperture for a clean, refined appearance. Available with transformer incorporated, transformer attached, and remote transformer configurations for new and old work installations. The series is adaptable to plaster, gypboard, wood, or acoustical ceilings. This series conforms to USA standards. A companion series that conforms to Asian and European standards is also available.

Two Lamp




M-2-LED/16-1-TI-REC-TR

Modular Multiples® Trimmed Series, two 16w LED modules, white housing, transformer incorporated, rectangular aperture, trimmed configuration shown.

Other configurations available.

[Download CSI drop-in spec template](#)



LAMPS and DIMENSIONS	A	B	C	D	E	F	G
LED506, LED513 / MR16LED / MR16	3-3/8" 86mm	4-7/8" 124mm	6-7/8" 175mm	8-3/8" 213mm	1'1" 330mm	10-1/2" 267mm	8" 203mm
LED708, 714, 716, 930 / AR111LED / AR111	7-1/4" 184mm	9-1/4" 235mm	1'2" 356mm	1'4" 406mm	1'5-1/2" 445mm	1'1-3/4" 349mm	8-1/2" 216mm
PAR38LED / PAR38	7-1/4" 184mm	9-1/4" 235mm	1'2-3/4" 375mm	1'4-3/4" 425mm	1'6-1/4" 464mm	1'1-3/4" 349mm	9-3/4" 248mm

Modular Multiples®

Trimmed

Recessed - New Work

Built to your specifications, these high-quality fixtures feature a trimmed aperture for a clean, refined appearance. Available with transformer incorporated, transformer attached, and remote transformer configurations for new and old work installations. The series is adaptable to plaster, gypboard, wood, or acoustical ceilings. This series conforms to USA standards. A companion series that conforms to Asian and European standards is also available.

Three Lamp




M-3-B-2-TI-REC-TR

Modular Multiples® Trimmed Series, three MR16 lamps, black housing, transformer incorporated, rectangular aperture, trimmed configuration shown.

Other configurations available.

[Download CSI drop-in spec template](#)



LAMPS and DIMENSIONS	A	B	C	D	E	F	G
LED506, LED513 / MR16LED / MR16	3-3/8" 86mm	4-7/8" 124mm	10-3/8" 264mm	11-7/8" 302mm	1'7-1/4" 489mm	10-1/2" 267mm	8" 203mm
LED708, 714, 716, 930 / AR111LED / AR111	7-1/4" 184mm	9-1/4" 235mm	1'9" 533mm	1'11" 584mm	2'0-1/2" 622mm	1'1-3/4" 349mm	8-1/2" 216mm
PAR38LED / PAR38	7-1/4" 184mm	9-1/4" 235mm	1'10-1/4" 565mm	2'0-1/4" 616mm	2'1-3/4" 654mm	1'1-3/4" 349mm	9-3/4" 248mm

Modular Multiples®

Trimmed

Recessed - New Work

Built to your specifications, these high-quality fixtures feature a trimmed aperture for a clean, refined appearance. Available with transformer incorporated, transformer attached, and remote transformer configurations for new and old work installations. The series is adaptable to plaster, gypboard, wood, or acoustical ceilings. This series conforms to USA standards. A companion series that conforms to Asian and European standards is also available.

Four Lamp




M-4-B-2-TI-REC-TR

Modular Multiples® Trimmed Series, four MR16 lamps, black housing, transformer incorporated, rectangular aperture, trimmed configuration shown.

Other configurations available.

[Download CSI drop-in spec template](#)



LAMPS and DIMENSIONS	A	B	C	D	E	F	G
LED506, LED513 / MR16LED / MR16	3-3/8" 86mm	4-7/8" 124mm	1' 1-7/8" 352mm	1'3-3/8" 391mm	2'1-1/2" 648mm	10-1/2" 267mm	8" 203mm
LED708, 714, 716, 930 / AR111LED / AR111	7-1/4" 184mm	9-1/4" 235mm	2'4" 711mm	2'6" 762mm	2'7-1/2" 800mm	1'1-3/4" 349mm	8-1/2" 216mm
PAR38LED / PAR38	7-1/4" 184mm	9-1/4" 235mm	2'5-3/4" 756mm	2'7-3/4" 806mm	2'9" 838mm	1'1- 3/4"349mm	9-3/4" 248mm





Modular Multiples®

Trimmed

Recessed - New Work

Built to your specifications, these high-quality fixtures feature a trimmed aperture for a clean, refined appearance. Available with transformer incorporated, transformer attached, and remote transformer configurations for new and old work installations. The series is adaptable to plaster, gypboard, wood, or acoustical ceilings. This series conforms to USA standards. A companion series that conforms to Asian and European standards is also available.

Four Lamp Square



M-4-B-2-TI-SQSQ-TR

Modular Multiples® Trimmed Series, four MR16 lamps, black housing, transformer incorporated, square aperture, square lamp configuration, trimmed configuration shown. Other configurations available.

[Download CSI drop-in spec template](#)

LAMPS and DIMENSIONS	A	B	C	D	E	F	G
LED506, LED513 / MR16LED / MR16	6-7/8" 213mm	8-3/8" 213mm	6-7/8" 175mm	8-3/8" 213mm	1'1" 330mm	1'4-1/2" 419mm	8" 203mm
LED708, 714, 716, 930 / AR111LED / AR111	1'2" 356mm	1'4" 406mm	1'2" 356mm	1'4" 406mm	1'5-1/2" 445mm	1'11-3/4" 603mm	8-1/2" 216mm
PAR38LED / PAR38	1'2-3/4" 375mm	1'4-3/4" 425mm	1'2-3/4" 375mm	1'4-3/4" 425mm	1'6-1/4" 464mm	2'0-1/4" 616mm	9-3/4" 248mm

Modular Multiples®

Trimmed

Recessed - New Work

Built to your specifications, these high-quality fixtures feature a trimmed aperture for a clean, refined appearance. Available with transformer incorporated, transformer attached, and remote transformer configurations for new and old work installations. The series is adaptable to plaster, gypboard, wood, or acoustical ceilings. This series conforms to USA standards. A companion series that conforms to Asian and European standards is also available.

Custom Mixed Lamp




M-2-D/1-G-2-TI-REC-TR

Modular Multiples® Trimmed Series, custom configuration, two AR111 lamps, one PAR30 HID lamp, black housing, transformer attached, rectangular aperture, trimmed configuration shown.

Other configurations available.

[Download CSI drop-in spec template](#)



LAMPS and DIMENSIONS	A	B	C	D	E	F	G	H
AR111 / PAR30-HID	7-1/4" 184mm	9-1/4" 235mm	21" 533mm	23" 584mm	9" 229mm	3" 76mm	24-1/2" 622mm	13-3/4" 349mm

Modular Multiples®

Trimmed®
Recessed
New/Old Work



This leaflet contains products covered under one or more of the following US Patent Numbers:

6,568,826B1	6,692,139B2
6,820,999B2	7,207,698B2
6,896,391B2	6,969,182B2
6,997,267B2	6,997,574B2
7,036,953B2	6,745,785B2
7,300,176B2	7,478,921B1
D520,666S	D530,038S
D537,553S	D819,857
D818,632	D818,624
D818,623	8,740,407
8,511,860	8,231,242
8,210,720	7,832,907

Modular International, Inc. produced a major portion of the lighting for the project shown. The photograph, however, is not intended to imply that the various owners of the projects endorse our products or use our products exclusively.

Modular International Inc.
3941 California Avenue
Pittsburgh, PA 15212
1-412-734-9000

www.modularinternational.com

Modular Multiples®

The Original Multiple Lamp Family of Fixtures

4

Trimmed

Recessed - New/Old Work



- Configurations:**
- 1, 2, 3, 4 light units standard
 - Custom configurations available

- Housing:**
- Fabricated 18 gauge steel supplied with adjustable mounting brackets
 - 14 gauge steel trim flange
 - Available for airtight or IC rated applications

- Finishes:**
- Powder coated - white or black standard
 - Custom colors available
 - Stainless steel / satin nickel available

- Electrical:**
- Internal electronic power supply(s) /transformer(s) / ballast(s)
 - Dimmable (not applicable on HID products)
 - One power supply / transformer per lamp allowing for multi-circuit wiring.
 - 120v and 277v available
 - Listed to UL1598 standards

Lamping:

Standard LED Modules

6w LED-506-6	12w LED-512-12	12w LED-512-22
8w LED-708-6	14w LED-714-12	14w LED-714-22
16w LED-716-12	16w LED-716-22	16w LED-716-45
30w LED-930-12	30w LED-930-22	30w LED-930-45

Direct Replacement LED or Legacy Lamps:

MR16LED (BLD)	MR16 HALOGEN (B)	MR16CMH (BH)
AR111LED (DLD)	AR111 HALOGEN (D)	CDMR111 (S)
PAR30LED (GLD)	PAR30 (G)	PAR30HID (H)
PAR38LED (JLD)	PAR38 (J)	PAR38HID (K)

Mounting:


- For applications where ceilings are currently installed.
- An opening is cut into the ceiling material to fit the Mounting Frame.
- Housing connected to 18 gauge galvanized steel transformer / wiring section via 24" flexible metal conduit
- Fixture wiring connections are made and fixture is inserted through the installed frame and secured with provided hardware

Options:






- Patented die-cast aluminum ring sets and locking devices
- Pull down yokes
- Shielding cones
- Filter media
 - LED modules accept one 1/8" thick filter
 - LED direct replacement and legacy lamps accept up to two 1/8" thick filters

**Model #
example:**

M-3-BLD-2-TA-REC-TR




[Download CSI
drop-in spec template](#)




Modular Multiples®


Trimmed TA Typical Installation




1 + 2 Light Transformer Housing



3 + 4 Light Transformer Housing



5 + 6 Light Transformer Housing



Modular Multiples®

Trimmed

Recessed - New/Old Work

Built to your specifications, these high-quality fixtures feature a trimmed aperture for a clean, refined appearance. Available with transformer incorporated, transformer attached, and remote transformer configurations for new and old work installations. The series is adaptable to plaster, gypboard, wood, or acoustical ceilings. This series conforms to USA standards. A companion series that conforms to Asian and European standards is also available.

One Lamp




M-1-BLD-2-TA-SQ-TR

Modular Multiples® Trimmed Series, one MR16LED lamp, black housing, transformer attached, square aperture, trimmed configuration shown.

Other configurations available.

[Download CSI drop-in spec template](#)



LAMPS and DIMENSIONS	A	B	C	D	E	F	G
LED506, LED513 / MR16LED / MR16	3" 76mm	4-1/2" 114mm	3" 76mm	4-1/2" 114mm	3-1/8" 79mm	3-1/2" 89mm	5" 127mm
LED708, 714, 716, 930 / AR111LED / AR111	7-1/4" 184mm	9-1/4" 235mm	7-1/4" 184mm	9-1/4" 235mm	7-1/2" 191mm	7-1/2" 191mm	6" 152mm

Modular Multiples®

Trimmed

Recessed - New/Old Work

Built to your specifications, these high-quality fixtures feature a trimmed aperture for a clean, refined appearance. Available with transformer incorporated, transformer attached, and remote transformer configurations for new and old work installations. The series is adaptable to plaster, gypboard, wood, or acoustical ceilings. This series conforms to USA standards. A companion series that conforms to Asian and European standards is also available.


Two Lamp



M-2-BLD-2-TA-REC-TR

Modular Multiples® Trimmed Series, two MR16LED lamps, black housing, transformer attached, rectangular aperture, trimmed configuration shown. Other configurations available.

[Download CSI drop-in spec template](#)



LAMPS and DIMENSIONS	A	B	C	D	E	F	G
LED506, LED513 / MR16LED / MR16	3" 76mm	4-1/2" 114mm	6-7/8" 175mm	8-3/8" 213mm	7-3/8" 187mm	3-1/8" 79mm	5" 127mm
LED708, 714, 716, 930 / AR111LED / AR111	7-1/4" 184mm	9-1/4" 235mm	1'2" 356mm	1'4" 406mm	1'2-1/4" 362mm	7-1/2" 191mm	6" 152mm



Modular Multiples®

Trimmed

Recessed - New/Old Work


Built to your specifications, these high-quality fixtures feature a trimmed aperture for a clean, refined appearance. Available with transformer incorporated, transformer attached, and remote transformer configurations for new and old work installations. The series is adaptable to plaster, gypboard, wood, or acoustical ceilings. This series conforms to USA standards. A companion series that conforms to Asian and European standards is also available.

Three Lamp



M-3-BLD2-TA-REC-TR

Modular Multiples® Trimmed Series, three MR16LED lamps, black housing, transformer attached, rectangular aperture, trimmed configuration shown. Other configurations available.



[Download CSI drop-in spec template](#)

LAMPS and DIMENSIONS	A	B	C	D	E	F	G
LED506, LED513 / MR16LED / MR16	3" 76mm	4-1/2" 114mm	10" 254mm	11-1/2" 292mm	10-1/2" 267mm	3-1/2" 89mm	5" 127mm
LED708, 714, 716, 930 / AR111LED / AR111	7-1/4" 184mm	9-1/4" 235mm	1'8-3/4" 527mm	1'10-3/4" 578mm	1'9" 533mm	7-1/2" 191mm	6" 152mm




Modular Multiples®

Trimmed

Recessed - New/Old Work

Built to your specifications, these high-quality fixtures feature a trimmed aperture for a clean, refined appearance. Available with transformer incorporated, transformer attached, and remote transformer configurations for new and old work installations. The series is adaptable to plaster, gypboard, wood, or acoustical ceilings. This series conforms to USA standards. A companion series that conforms to Asian and European standards is also available.

Four Lamp



M-4-D-2-TA-REC-TR

Modular Multiples® Trimmed Series, four AR111 lamps, black housing, transformer attached, rectangular aperture, trimmed configuration shown.

Other configurations available.

[Download CSI drop-in spec template](#)

LAMPS and DIMENSIONS	A	B	C	D	E	F	G
LED506, LED513 / MR16LED / MR16	3" 76mm	4-1/2" 114mm	1'1-7/8" 352mm	1'3-3/8" 391mm	1'2-3/8" 365mm	3-1/8" 79mm	5" 127mm
LED708, 714, 716, 930 / AR111LED / AR111	7-1/4" 184mm	9-1/4" 235mm	2'3-1/2" 699mm	2'5-1/2" 749mm	2'3-3/4" 705mm	7-1/2" 191mm	6" 152mm

Modular Multiples®

Trimmed

Recessed - New/Old Work

Built to your specifications, these high-quality fixtures feature a trimmed aperture for a clean, refined appearance. Available with transformer incorporated, transformer attached, and remote transformer configurations for new and old work installations. The series is adaptable to plaster, gypboard, wood, or acoustical ceilings. This series conforms to USA standards. A companion series that conforms to Asian and European standards is also available.

Four Lamp Square




M-4-BLD-2-TA-SQ-TR

Modular Multiples® Trimmed Series, four MR16LED lamps, black housing, transformer attached, square aperture, trimmed configuration shown.

Other configurations available.

[Download CSI drop-in spec template](#)



LAMPS and DIMENSIONS	A	B	C	D	E	F	G
LED506, LED513 / MR16LED / MR16	6-7/8" 175mm	8-3/8" 213mm	8-3/8" 213mm	1'3-3/8" 391mm	7-1/8" 181mm	7-1/8" 181mm	5" 127mm
LED708, 714, 716, 930 / AR111LED / AR111	1'2" 356mm	1'2" 356mm	1'4" 406mm	2'3-3/4" 705mm	1'2-1/4" 362mm	1'2-1/4" 362mm	6" 152mm



Modular Multiples®

Trimmed

Recessed - New/Old Work

Built to your specifications, these high-quality fixtures feature a trimmed aperture for a clean, refined appearance. Available with transformer incorporated, transformer attached, and remote transformer configurations for new and old work installations. The series is adaptable to plaster, gypboard, wood, or acoustical ceilings. This series conforms to USA standards. A companion series that conforms to Asian and European standards is also available.

Custom Six Lamp



M-6-B-2-TA-REC-TR

Modular Multiples® Trimmed Series, six MR16 lamps, black housing, transformer attached, rectangular aperture, trimmed configuration shown.

Other configurations available.

[Download CSI drop-in spec template](#)

LAMPS and DIMENSIONS	A	B	C	D	E	F	G
LED506, LED513 / MR16LED / MR16	3" 76mm	4-1/2" 114mm	20-7/8" 530mm	22-3/8" 568mm	21-1/8" 537mm	3-1/8" 79mm	5" 127mm
LED708, 714, 716, 930 / AR111LED / AR111	7-1/4" 184mm	9-1/4" 235mm	41" 1041mm	43" 1092mm	41-1/4" 1048mm	7-1/2" 191mm	6" 152mm

Modular Multiples®


The Original Multiple Lamp Family of Fixtures



Standard LED Modules


LED-506-6

337 Lumens, 6w, 6° Optics, 2700°K, 95CRI




LED-512-12

591 Lumens, 12w, 12° Optics, 2700°K, 95CRI




LED-512-22

646 Lumens, 12w, 22° Optics, 2700°K, 95CRI




LED-708-6

433 Lumens, 8w, 6° Optics, 2700°K, 95CRI




LED-714-12

1189 Lumens, 14w, 12° Optics, 2700°K, 95CRI




LED-714-22

1160 Lumens, 14w, 22° Optics, 2700°K, 95CRI




LED-716-12

1485 Lumens, 16w, 12° Optics, 2700°K, 95CRI




LED-716-22

1406 Lumens, 16w, 22° Optics, 2700°K, 95CRI




LED-716-45

1351 Lumens, 16w, 45° Optics, 2700°K, 95CRI




LED-930-12

2003 Lumens, 30w, 12° Optics, 3000°K, 95CRI




LED-930-22

2119 Lumens, 30w, 22° Optics, 3000°K, 95CRI



LED-930-45

2328 Lumens, 30w, 45° Optics, 3000°K, 95CRI




Modular Multiples®

Fixture Options


Modular accessories are used individually or in inventive combinations to shield brightness, reduce glare, vary beam patterns, retain direction, and alter color. Dimensions of all fixture options vary with lamp size.

Ring Sets and Locking Devices (PATENTED)


ADD -LM TO END OF MODEL NUMBER



BOTTOM VIEW



FRONT VIEW




SIDE VIEW



Extendable Yokes

ADD -EY TO END OF MODEL NUMBER

RETRACTED



EXTENDED




Modular Multiples®

Fixture Options

Modular accessories are used individually or in inventive combinations to shield brightness, reduce glare, vary beam patterns, retain direction, and alter color. Fixture option dimensions vary with lamp size.

Shielding Options

ADD SHIELDING OPTION CODE (BELOW) TO END OF MODEL NUMBER



FILTER RING (STANDARD)

SHIELDING CONE (-SC)

SHIELDING CYLINDER (-CY)


WALL WASH CONE (-WWC)

Filter Media


ADD FILTER MEDIA CODE (BELOW) TO END OF MODEL NUMBER

LED modules accept one 1/8" thick filter. LED direct replacement and legacy lamps accept up to two 1/8" thick filters.


CLEAR
GLASS (-CG)




DIFFUSING
SPREAD (-DS)




CUBE CELL
LOUVER (-CL)




HEXCELL
LOUVER (-HL)




LINEAR
SPREAD (-LS)




PRISMATIC WIDE
SPREAD (-PS)




SATIN ETCHED
(-SE)



UV BLOCKING
(-UB)



DICHROIC



RED
(-DR)

MAGENTA
(-DM)

BLUE
(-DB)

GREEN
(-DG)

AMBER
(-DA)

YELLOW
(-DY)

PEACH
(-DP)